
Technical Sheet

EA444/2PB


Black painted light reinforced angle bracket

Light reinforced black angle brackets are used to assemble small structural joinery for internal and external applications.









Wood to wood connection.

Features

Material

- Pre-galvanised mild steel,
- Painted black RAL9005,
- 2 mm thickness

Benefits

- Black colour to be discreet,
- Multiple applications...

Applications

Header member

- **Supporting member:** solid wood, composite lumber, glued-laminated wood, triangular trusses, profiles, etc.
- **Supported member:** wood, concrete, steel, etc.

For Use With


- Interior fittings.
- Furniture.
- Small frames, etc.


Technical Sheet

EA444/2PB

Black painted light reinforced angle bracket

Technical Data





Product dimensions

Reference	konektor rozměry						
	ostatní	rozměry výrobku[mm]				příruba B	otvory příruba C
	hmotnost[kg]	A[mm]	B[mm]	C[mm]	tloušťka[mm]	kulatý Ø	kulatý Ø
EA444/2PB-R	0.86	40	40	40	2	3	3

EA444/2PB

Black painted light reinforced angle bracket

Installation

Fixing

On wood:


- 3.75 x 30mm square twist nail.
- CNA annular ring-shank nails 4.0 mm.
- CSA screw 5.0 mm.

On concrete:

- HIPC 6-40/10 drive anchors or HIPC 8-60/20.


On metal:

- Bolts.
- HR bolts.
- Rivets, etc.



EA444/2PB
Black painted light reinforced angle bracket

Možnosti



Copyright by Simpson Strong-Tie®