
Technical Sheet

SCMF
Floor Connector

The SCMF storey connector is a component of the two-part tie rod and can be quickly and flexibly adapted to the storey transition heights thanks to the continuous perforation.





Features

Material

- Pre-galvanised steel S250GD + Z275 according to standard NF EN 10346
- Thickness 2 mm

Adventages


- All lengths possible in 20 mm increments.
- Quick connection of the connecting plates of the two-part tie rods with self-drilling EJOT screws.

Applications

Fasteners

EJOT screws - JT2-3-5,5x25

Technical Data



Dimension

Reference	konektor rozměry					
	rozměry výrobku[mm]				otvory[mm]	
	A[mm]	B[mm]	Tloušťka[mm]	průměr[mm]	Crosswise[mm]	Lengthwise[mm]
SCMF35/B-X	35	1)	2	6	20	20
SCMF55/B-X	55	1)	2	6	36	20

1) according to customer requirements in 20 mm increments

Characteristic values

Reference	Ties únosnost	
	výrobek characteristic capacities - dřevo C24[kN]	
	počet of Ejot-Scrwes 1)[mm]	$R_{1,k}$[kN]
SCMF35/B-X	2x2	12,8/kmod
SCMF55/B-X	2x4	25,6/kmod

1)The EJOT screws must always be arranged symmetrically.

Copyright by Simpson Strong-Tie®