Technical Sheet

DSPROA4


Hardwood Decking Screw - Stainless Steel A4

Made for hardwood decking such as Cumaro, Bankirai and others. Can be used in Marine environments. Needs pre-drilling with 4 mm drill and pre-countersinking close to the edge.









Features

Material

- Stainless Steel A4

Features:

- 6 lobe drive
- Double threaded
- Chisel point

Applications

Applications:


- Hardwood decking boards to wood

Suitable for:

- Outdoor decking applications

DSPROA4
Hardwood Decking Screw - Stainless Steel A4

Technical Data



Rozměry

Reference	Fasteners rozměry						
	ostatní	rozměry výrobku[mm]					
	hmotnost[kg]	d[mm]	l[mm]	d_h[mm]	l_{g1} [mm]	l_{g2} [mm]	Driver Bit[mm]
DSPROA45.5X50	0.005	5.5	50	7	22.5	10.5	T-25
DSPROA45.5X60	0.005	5.5	60	7	27.5	10.5	T-25
DSPROA45.5X70	0.005	5.5	70	7	32.5	10.5	T-25
DSPROA45.5X80	0.006	5.5	80	7	37.5	10.5	T-25

Product characteristic properties

Reference	šroub parametry			
	charakteristické parametry			
	Characteristic Yield Moment – $M_{y,k}$[Nm]	Characteristic withdrawal parameter - $f_{ax,k,90°}$[N/mm²]	Characteristic hlava pull-through parameter - $f_{head,k}$[N/mm²]	Characteristic tensile únosnost - $f_{tens,k}$[kN]
DSPROA45.5X50	7585	12.8	31.8	7.8
DSPROA45.5X60	7585	12.8	31.8	7.8
DSPROA45.5X70	7585	12.8	31.8	7.8
DSPROA45.5X80	7585	12.8	31.8	7.8

Copyright by Simpson Strong-Tie®