Technical Sheet

QD76KE

Multifunkční nástavec Quik drive QD76KE

Teflonový multifunkční nástavec pro upevnění dřevěné podlahy a sádrokartonu. Quik Drive® používá šrouby o délce 25 až 76 mm na (včetně 3 hlavy).







Nez acier pour vis de 38 à 64 mm.



Features

Material

- Nástroj Teflon®, nevyžaduje mazání.

Vorteile

- Umístění nástroje přes nástavce na elektrický šroubovák a možnost prodloužení
- Montáž na elektrický šroubovák nebo rozšíření pouhým zaklapnutím.
- Obsahuje Klíč 191E-RC.

Available kits

obsahuje: nástavec QD76 pro páskované šrouby (s vestavěným-in bit držákem 191E-RC) 3 výměnnými vodícími hřídelí: # 2: Kombinovaná vodicí hřídel pro šrouby 25 až 51 mm: zakřivený podavač zásobníku # 2.5: kovová vodící hřídel pro šrouby 38 až 64 mm # 3: kovová vodící hřídel pro šrouby 76 mm

- Uzavřené bity: 2x BIT2PE, 1x BIT3SE, 1x BIT2SE, 1x a 1x BIT2SUE
- Rozšíření QDEXTE pro šrouby stojící
- Robustní kufřík na nářadí

Applications

Anwendungsbereich

- Multi-application collated screwing

Technical Sheet

QD76KE

Multifunkční nástavec Quik drive QD76KE

Technical Data

Areas of use

Reference	Fasteners rozměry
	QD informace
	Ancrages
QD76KE	CBSDQ, DWC, DWF, DWFSD, MTH, WSC, WSV, RTFSD, RDPF, RDWF

Installation



1. Remove the sleeve from your screwdriver



2. Remove the nozzle



3. Install the adapter



4. Insert the chuck



5. Engage the magazine on the chuck and snap it onto the adapter



6. Insert the strip of screws with the point facing upwards: your screwdriver is ready !

Copyright by Simpson Strong-Tie®