Technical Sheet

BAN09
Windbracing Strap

BAN09 windbracing straps can be used for anchoring and bracing of roof constructions. The engineered "strong-holes" ensures a very light 0,9 mm strap with the same capacities as a 2 mm strap. The thin material makes the strap easy to lift and handle on the job site. And it is easy to cut with metal shears.







Features

Material

c


Vorteile


- Reinforced holes offer enhanced strap tensile capacity
- Very ligth weigt but strong
- Easy to cut with metal shears

Technical Sheet

BAN09
Windbracing Strap

Technical Data





Rozměry a typické hodnoty

Reference	konektor rozměry					
	ostatní		rozměry výrobku[mm]			otvory[mm]
	množství v krabici	hmotnost[kg]	Šířka[mm]	Délka[mm]	Tloušťka[mm]	Ø[mm]
BAN094050	1.0	12.9	40	50	0.9	5

Product capacities


Reference	Straps únosnost		
	Characteristic capacities - dřevo C24[kN]		
	$R_{1,k}$[kN]		
	ocel	mit CNA4,0x40	mit CNA4,0x50
BAN094050	17.8	1.83 x n	2.22 x n

n = effective number of nails in the row according to Eurocode 5 – 8.3.1.1 (8)

Installation

Fixation

c



Copyright by Simpson Strong-Tie®